

Scientists have determined the threshold energy level for human observers exposed to pulsed 2450-MHz fields (0.5-to 32 micron pulse widths). They found that, regardless of the peak of the power density and the pulse width, the per-pulse threshold for a normal subject is near 20 mJ/kg. The average elevation of brain temperature associated with a just-perceptible pulse was estimated to be about 5×10^{-6} C.

Time to Onset

The physical nature of this thermoelastic expansion dictates that the sounds are heard as the individual pulses are absorbed. Thus, the effect is immediate (within milliseconds). Humans have been exposed to RF energy that resulted in the production of sounds.

Duration of Effect

Microwave hearing lasts only as long as the exposure. There is no residual effect after cessation of RF energy.

Tunability

The phenomenon is tunable in that the characteristic sounds and intensities of those sounds depend on the characteristics of the RF energy as delivered. Because the frequency of the sound heard is dependent on the pulse characteristics of the RF energy, it seems possible that this technology could be developed to the point where words could be transmitted to be heard like the spoken word, except that it could only be heard within a person's head. In one experiment, communication of the words from one to ten using "speech modulated" microwave energy was successfully demonstrated. Microphones next to the person experiencing the voice could not pick up the sound. Additional development of this would open up a wide range of possibilities.

Distribution of Human Sensitivities to Desired Effects

Because the phenomenon acts directly on cochlear processes, the thermoelastic pressure waves produce sounds of varying frequency. Many of the tests run to evaluate the phenomenon produced sounds in the 5 kHz range and higher. Because humans are known to experience a wide range of hearing loss due to cochlear damage, it is possible that some people can hear RF induced sounds that others with high frequency hearing loss cannot. Thus, there is a likely range of sensitivity, primarily based on the type of pulse and the condition of the cochlea. Bilateral destruction of the cochlea has been demonstrated to abolish all RF-induced auditory stimuli.

Recovery/Safety

Humans have been subjected to this phenomenon for many years. The energy deposition required to produce this effect is so small that it is not considered hazardous experimentation when investigating responses at the just-perceptible levels.